

Peerless Chain Co.

1416 E. Sanborn St.,

Winona MN 55987

Phone: 507-457-9100 • **Fax:** 800-356-1149**Email:** custserv@peerlesschain.com • **Website:** www.peerlesschain.com**ACCO G43 Domestic High Test ISO Chain**

A high tensile strength carbon steel anchor (windlass) chain with an ISO short link. The short link makes it more flexible and ideally suited as windlass chain. Check fit or contact windlass manufacturer before purchase. This extra thick hot dip galvanized finish is recommended for all marine applications.

Results 1 - 25 of 33

Item #	Finish	Size	Wire Diameter	Inside Dim. Length (Nominal)	Inside Dim. Width (Min)	Qty. Per Drum	Weight	Working Load Limit	Working Load Limit
500110401	Self Colored	1/4 in	0.274 in	0.845 in	0.410 in	400	293 lbs	2600 lbs	1180 kg
500191733	Hot Galvanized	1/4 in	0.274 in	0.845 in	0.410 in	3600	2628 lbs	2600 lbs	1180 kg
500140402	Hot Galvanized	1/4 in	0.274 in	0.845 in	0.410 in	800	586 lbs	2600 lbs	1180 kg
501340401	Hot Galvanized	1/4 in	0.274 in	0.845 in	0.410 in	134	98 lbs	2600 lbs	1180 kg
501310401	Self Colored	1/4 in	0.274 in	0.845 in	0.410 in	134	98 lbs	2600 lbs	1180 kg
500140401	Hot Galvanized	1/4 in	0.274 in	0.845 in	0.410 in	400	293 lbs	2600 lbs	1180 kg
500110402	Self Colored	1/4 in	0.274 in	0.845 in	0.410 in	800	586 lbs	2600 lbs	1180 kg
501340501	Hot Galvanized	5/16 in	0.329 in	1.030 in	0.500 in	275	285 lbs	3900 lbs	1770 kg
500110502	Self Colored	5/16 in	0.329 in	1.030 in	0.500 in	550	570 lbs	3900 lbs	1770 kg
500140501	Hot Galvanized	5/16 in	8 mm 0.330 in	1.030 in	0.500 in	N/A	N/A	3900 lbs	N/A
500110501	Self Colored	5/16 in	0.329 in	1.030 in	0.500 in	275	285 lbs	3900 lbs	1770 kg
500140502	Hot Galvanized	5/16 in	0.329 in	1.030 in	0.500 in	550	570 lbs	3900 lbs	1770 kg
501310501	Self Colored	5/16 in	0.329 in	1.030 in	0.500 in	90	93 lbs	3900 lbs	1770 kg
500191734	Hot Galvanized	5/16 in	0.330 in	1.030 in	0.500 in	2800	2903 lbs	3900 lbs	1770 kg
500110632	Self Colored	3/8 in	0.394 in	1.220 in	0.600 in	400	595 lbs	5400 lbs	2450 kg
501310601	Self Colored	3/8 in	0.394 in	1.220 in	0.600 in	64	95 lbs	5400 lbs	2540 kg
500140631	Hot Galvanized	3/8 in	0.394 in	1.220 in	0.600 in	200	297 lbs	5400 lbs	2450 kg
500110631	Self Colored	3/8 in	0.394 in	1.220 in	0.600 in	200	297 lbs	5400 lbs	2450 kg
500140632	Hot Galvanized	3/8 in	0.394 in	1.220 in	0.600 in	400	595 lbs	5400 lbs	2450 kg
501340601	Hot Galvanized	3/8 in	0.394 in	1.220 in	0.600 in	64	95 lbs	5400 lbs	2450 kg
500191735	Hot Galvanized	3/8 in	0.394 in	1.220 in	0.600 in	1800	2672 lbs	5400 lbs	2450 kg
500140702	Hot Galvanized	7/16 in	0.467 in	1.400 in	0.660 in	300	645 lbs	7200 lbs	3266 kg
500110701	Self Colored	7/16 in	0.467 in	1.400 in	0.660 in	150	322 lbs	7200 lbs	3266 kg
500140701	Hot Galvanized	7/16 in	0.467 in	1.400 in	0.660 in	150	332 lbs	7200 lbs	3266 kg
500110702	Self Colored	7/16 in	0.467 in	1.400 in	0.660 in	300	645 lbs	7200 lbs	3266 kg

Results 1 - 25 of 33